


DIN 228A	typ W		
$\lambda=45^\circ$ $\gamma=20^\circ$	HSS	410940	
$\lambda=45^\circ$ $\gamma=22^\circ$	HSS Co5	410245	



	Uygulama / Usage / Applikation / Zastosowanie												
410940	1	2	3	4	5	6	7	8	9	10	11	12	13
410245	1	2	3	4	5	6	7	8	9	10	11	12	13



D k 10**	I	L	MK	Z	CODE	CODE
10	22	92	1	3	—	410245.100
12	26	111	2	3	—	410245.120
16	32	117	2	3	—	410245.160
20	38	123	2	3	—	410245.200
22	38	123	2	3	—	410245.220
24	45	147	3	3	—	410245.240
25	45	147	3	4	—	410245.250
25	50	154	3	4	410940.250	—
26	45	147	3	4	—	410245.260
28	45	147	3	4	—	410245.280
28	50	154	3	4	410940.280	—
30	45	147	3	4	—	410245.300
30	50	154	3	4	410940.300	—
32	53	178	4	4	410940.320	410245.320
36	53	178	4	4	410940.360	410245.360
40	63	188	4	4	410940.400	410245.400
45	63	188	4	4	410940.450	410245.450
50	70	228	5	5	410940.500	—
50	75	233	5	5	—	410245.500
63	80	241	5	6	410940.630	—
63	90	248	5	6	—	410245.630

*/ ≠ DIN 845

**/ 410940 – js 14