



Závitové kruhové čelisti Circular dies Schneideisen Плашки

M

Metrický závit
Standard metric thread
Metrische Regelgewinde
Метрическая резьба

MF

Jemný metrický závit
Fine metric thread
Metrische Feingewinde
Мелкая метрическая резьба



1,5P

	P	D	h	S		code ¹⁾
M 1	0,25	16	5	3	1,0	XXX 010
M 1,1	0,25	16	5	3	1,1	XXX 011
M 1,2	0,25	16	5	3	1,2	XXX 012
M 1,4	0,3	16	5	3	1,4	XXX 014
M 1,6	0,35	16	5	3	1,6	XXX 016
M 1,8	0,35	16	5	3	1,8	XXX 018
M 2	0,4	16	5	3	2,0	XXX 020
M 2,2	0,45	16	5	3	2,2	XXX 022
M 2,5	0,45	16	5	3	2,5	XXX 025
M 2,5	0,35	16	5	3	2,5	XXX 026
M 3	0,5	20	5	3	3,0	XXX 030
M 3	0,35	20	5	3	3,0	XXX 031
M 3,5	0,6	20	5	3	3,5	XXX 035
M 3,5	0,35	20	5	3	3,5	XXX 036
M 4	0,7	20	5	3	4,0	XXX 040
M 4	0,5	20	5	3	4,0	XXX 041
M 4,5	0,5	20	5	3	4,5	XXX 046
M 5	0,8	20	7	4	5,0	XXX 050
M 5	0,5	20	5	4	5,0	XXX 051
M 5,5	0,5	20	5	4	5,5	XXX 056
M 6	1	20	7	4	6,0	XXX 060
M 6	0,75	20	7	4	6,0	XXX 061
M 7	1	25	9	4	7,0	XXX 070
M 7	0,75	25	9	4	7,0	XXX 071
M 8	1,25	25	9	4	8,0	XXX 080
M 8	1	25	9	4	8,0	XXX 081
M 8	0,75	25	9	4	8,0	XXX 082
M 9	1,25	25	9	4	9,0	XXX 090
M 9	1	25	9	4	9,0	XXX 091
M 9	0,75	25	9	4	9,0	XXX 092
M 10	1,5	30	11	4	10,0	XXX 100
M 10	1,25	30	11	4	10,0	XXX 101
M 10	1	30	11	4	10,0	XXX 102
M 10	0,75	30	11	4	10,0	XXX 103
M 11	1,5	30	11	5	11,0	XXX 110
M 11	1	30	11	5	11,0	XXX 111
M 11	0,75	30	11	5	11,0	XXX 112
M 12	1,75	38	14	4	12,0	XXX 120
M 12	1,5	38	10	4	12,0	XXX 121
M 12	1,25	38	10	4	12,0	XXX 122
M 12	1	38	10	4	12,0	XXX 123
M 14	2	38	14	5	14,0	XXX 140
M 14	1,5	38	10	5	14,0	XXX 141
M 14	1,25	38	10	5	14,0	XXX 142
M 14	1	38	10	5	14,0	XXX 143
M 15	1,5	38	10	5	15,0	XXX 151
M 15	1	38	10	5	15,0	XXX 152
M 16	2	45	18	5	16,0	XXX 160
M 16	1,5	45	14	5	16,0	XXX 161
M 16	1	45	14	5	16,0	XXX 162
M 17	1,5	45	14	5	17,0	XXX 171
M 17	1	45	14	5	17,0	XXX 172
M 18	2,5	45	18	5	18,0	XXX 180
M 18	2	45	14	5	18,0	XXX 181
M 18	1,5	45	14	5	18,0	XXX 182
M 18	1	45	14	5	18,0	XXX 183
M 20	2,5	45	18	6	20,0	XXX 200
M 20	2	45	14	6	20,0	XXX 201
M 20	1,5	45	14	6	20,0	XXX 202
M 20	1	45	14	6	20,0	XXX 203

Materiál: NO:
HSS, HSSE - dle požadavku
Provedení: závit lapovaný
do M 26
Závit: pravý, levý
Licování: 6g (6h, 6e - dle
požadavku zákazníka)

Material: CS:
HSS, HSSE - on request
Execution: lapped thread
to M 26
Thread: right-hand, left-hand
Tolerance: 6g (6h, 6e - on
request)

Werkstoff: WS:
HSS, HSSE - nach dem
Anspruch
Ausführung: geläpftes Gewinde
bis M 26
Gewinde: rechts, links
Toleranz: 6g (6h, 6e - nach dem
Anspruch)

Материал: NO:
HSS, HSSE - по заказу
Изготовлено: резьба
шлифованная до M 26
Резьба: правая, левая
Подгонка: 6g (6h, 6e - по
заказу)





Závitové kruhové čelisti Circular dies Schneideisen Плашки

M

Metrický závit
Standard metric thread
Metrische Regelgewinde
Метрическая резьба

MF

Jemný metrický závit
Fine metric thread
Metrische Feingewinde
Мелкая метрическая резьба



1,5P

	P	D	h	S		code ^{*)}
M 22	2,5	55	22	5	22,0	XXX 220
M 22	2	55	16	5	22,0	XXX 221
M 22	1,5	55	16	5	22,0	XXX 222
M 22	1	55	16	5	22,0	XXX 223
M 24	3	55	22	6	24,0	XXX 240
M 24	2	55	16	6	24,0	XXX 241
M 24	1,5	55	16	6	24,0	XXX 242
M 24	1	55	16	6	24,0	XXX 243
M 25	1,5	55	16	6	25,0	XXX 251
M 26	1,5	55	16	6	26,0	XXX 261
M 27	3	65	25	6	27,0	XXX 270
M 27	2	65	18	6	27,0	XXX 271
M 27	1,5	65	18	6	27,0	XXX 272
M 27	1	65	18	6	27,0	XXX 273
M 28	2	65	18	6	28,0	XXX 281
M 28	1,5	65	18	6	28,0	XXX 282
M 30	3,5	65	25	7	30,0	XXX 300
M 30	2	65	18	6	30,0	XXX 301
M 30	1,5	65	18	6	30,0	XXX 302
M 30	1	65	18	6	30,0	XXX 303
M 32	1,5	65	18	7	32,0	XXX 321
M 33	3,5	65	25	8	33,0	XXX 330
M 33	2	65	18	8	33,0	XXX 331
M 33	1,5	65	18	8	33,0	XXX 332
M 35	1,5	65	18	9	35,0	XXX 351
M 36	4	65	25	9	36,0	XXX 360
M 36	3	65	25	9	36,0	XXX 361
M 36	2	65	18	9	36,0	XXX 362
M 39	4	75	30	8	39,0	XXX 390
M 39	3	75	30	8	39,0	XXX 391
M 39	2	75	20	8	39,0	XXX 392
M 39	1,5	75	20	8	39,0	XXX 393
M 40	1,5	75	20	8	40,0	XXX 401
M 42	4,5	75	30	9	42,0	XXX 420
M 42	3	75	30	9	42,0	XXX 421
M 42	2	75	20	9	42,0	XXX 422
M 42	1,5	75	20	9	42,0	XXX 423
M 45	4,5	90	36	8	45,0	XXX 450
M 45	3	90	36	8	45,0	XXX 451
M 45	2	90	22	8	45,0	XXX 452
M 45	1,5	90	22	8	45,0	XXX 453
M 48	5	90	36	8	48,0	XXX 480
M 48	3	90	36	8	48,0	XXX 481
M 48	2	90	22	8	48,0	XXX 482
M 48	1,5	90	22	8	48,0	XXX 483
M 50	1,5	90	22	9	50,0	XXX 501
M 52	5	90	36	9	52,0	XXX 520
M 52	3	90	36	9	52,0	XXX 521
M 52	2	90	22	9	52,0	XXX 522
M 52	1,5	90	22	9	52,0	XXX 523

^{*)} 210 XXX - NO / CS / WS

^{*)} 240 XXX - HSS pravý závit / right hand thread / rechts Gewinde / правая резьба

^{*)} 249 XXX - HSS pravý závit s povlakem / right-hand thread with coating / rechts Gewinde mit Beschichtung / правая резьба с покрытием

^{*)} 250 XXX - HSS levý závit / left hand thread / links Gewinde / левая резьба

^{*)} 270 XXX - HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружек

^{*)} 280 XXX - HSS LH s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружек

^{*)} 290 XXX - HSSE pravý závit - pouze do M 30 / right hand thread - only to M 30 / rechts Gewinde - nur bis M 30 / правая резьба - только до M 30

^{*)} 295 XXX - HSSE s lamačem třísek - pouze do M 30 / with spiral point - only to M 30 / mit Schälanschnitt - nur bis M 30 / с ломателем стружек - только до M 30

^{*)} 300 XXX - HSSE s lamačem třísek - nerez - pouze do M 30 / with spiral point - Stainless steel - only to M 30 / mit Schälanschnitt - Rostfreistähle - nur bis M 30 / с ломателем стружек - нержавейка - только до M 30

Materiál: NO:
HSS, HSSE - dle požadavku
Provedení: závit lapovaný
do M 26
Závit: pravý, levý
Licování: 6g (6h, 6e - dle
požadavku zákazníka)

Material: CS:
HSS, HSSE - on request
Execution: lapped thread
to M 26
Thread: right-hand, left-hand
Tolerance: 6g (6h, 6e - on
request)

Werkstoff: WS:
HSS, HSSE - nach dem
Anspruch
Ausführung: geläpftes Gewinde
bis M 26
Gewinde: rechts, links
Toleranz: 6g (6h, 6e - nach dem
Anspruch)

Материал: NO:
HSS, HSSE - по заказу
Изготовлено: резьба
шлифованная до M 26
Резьба: правая, левая
Подрезка: 6g (6h, 6e - по
заказу)

