



Závitové kruhové čelisti
Circular dies
Schneideisen
Плашки

G

Trubkový závit
 Pipe thread
 Rohrgewinde
 Трубная резьба



1,5P

	z/1"	P	D	h	S		code ^{*)}
G 1/16"	28	0,907	25	9	4	7,7	XXX 116
G 1/8"	28	0,907	30	11	4	9,7	XXX 180
G 1/4"	19	1,337	38	10	5	13,1	XXX 140
G 3/8"	19	1,337	45	14	5	16,6	XXX 380
G 1/2"	14	1,814	45	14	6	20,9	XXX 120
G 5/8"	14	1,814	55	16	6	22,9	XXX 580
G 3/4"	14	1,814	55	16	6	26,4	XXX 340
G 7/8"	14	1,814	65	18	6	30,2	XXX 780
G 1"	11	2,309	65	18	8	32,2	XXX 100
G 1 1/8"	11	2,309	75	20	8	38,8	XXX 118
G 1 1/4"	11	2,309	75	20	9	41,9	XXX 114
G 1 3/8"	11	2,309	90	22	8	44,3	XXX 138
G 1 1/2"	11	2,309	90	22	8	47,8	XXX 112
G 1 3/4"	11	2,309	105	22	8	53,7	XXX 134
G 2"	11	2,309	105	22	8	59,6	XXX 200

^{*)} 212 XXX - NO / CS / WS

^{*)} 242 XXX - HSS

^{*)} 272 XXX - HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружек

^{*)} 292 XXX - HSSE

^{*)} 293 XXX - HSSE VA - na nerez / stainless steel / Rostfreistähle / нержавеющейка

*Materiál: NO;
 HSS, HSSE - dle požadavku
 Provedení: závit lapovaný
 do G 3/4"
 Závit: pravý
 Licování: třída A*

*Material: CS;
 HSS, HSSE - on request
 Execution: lapped thread to
 G 3/4"
 Thread: right-hand
 Tolerance: class A*

*Werkstoff: WS;
 HSS, HSSE - nach dem
 Anspruch
 Ausführung: geläpftes Gewinde
 bis G 3/4"
 Gewinde: rechts
 Toleranz: Klasse A*



*Material: NO;
 HSS, HSSE - по заказу
 Изготовлено: резьба
 шлифованная до G 3/4"
 Резьба: правая
 Подгонка: класс А*



**Závitové kruhové
čelisti
Circular dies
Schneideisen
Плашки**

UNC

Unifikovaný hrubý závit
Unified coarse thread
Unified-Grobgewinde
Унифицированная чёрная резьба



1,5P

	z/1"	P	D	h	S		code ^{*)}
4	40	0,635	20	5	3	2,8	XXX 004
5	40	0,635	20	5	3	3,1	XXX 005
6	32	0,794	20	7	3	3,4	XXX 006
8	32	0,794	20	7	3	4,1	XXX 008
10	24	1,058	20	7	3	4,7	XXX 010
12	24	1,058	20	7	4	5,4	XXX 012
1/4	20	1,270	20	7	4	6,2	XXX 140
5/16	18	1,411	25	9	4	7,8	XXX 516
3/8	16	1,588	30	11	4	9,4	XXX 380
7/16	14	1,814	30	11	5	10,95	XXX 716
1/2	13	1,954	38	14	5	12,5	XXX 120
9/16	12	2,117	38	14	5	14,1	XXX 916
5/8	11	2,309	45	18	5	15,7	XXX 580
3/4	10	2,540	45	18	6	18,8	XXX 340
7/8	9	2,822	55	22	5	22,0	XXX 780
1	8	3,175	55	22	6	25,1	XXX 100

^{*)} 215 XXX - NO / CS / WS

^{*)} 245 XXX - HSS

^{*)} 275 XXX - HSS s lamačem třísek / with spiral point / mit Schälanschnitt / с ломателем стружек

*Materiál: NO;
HSS, HSSE - dle požadavku
Provedení: závit lapovaný
Závit: pravý
Licování: 2A*

*Material: CS;
HSS, HSSE - on request
Execution: lapped thread
Thread: right-hand
Tolerance: 2A*

*Werkstoff: WS;
HSS, HSSE - nach dem
Anspruch
Ausführung: geläpftes Gewinde
Gewinde: rechts
Toleranz: 2A*

*Material: NO;
HSS, HSSE - по заказу
Изготовлено: резьба
шлифованная
Резьба: правая
Подгонка: 2A*

